Metalux

Product Selection Guide





a (Signify business

Metalux

Celebrating 50+ years, Metalux offers an extensive line of LED lighting products including recessed, linear and industrial fixtures.

Metalux's complete family of luminaires are dedicated to the latest solid state lighting and driver technology for optimal performance and energy efficiency.

Metalux delivers innovation, quality, product availability, and responsiveness all with an affordable value proposition.



The product selection guides are simple yet powerful tools to help assist with product comparisons and selection based on features, performance and value.

- Commercial LED Recessed Panels and Troffers
- Commercial LED Linear Ambient Strips and Wraps
 - **Industrial LED High Bay**
 - **Industrial LED Vaportite**











Good _

Click to	on products learn more									
		Backlit CGT	Backlit CGTS ²	Edgelit FP	Edgelit FPS	Backlit MMS	Backlit CGTX	Edgelit FPX	Backlit CGSB	Surround SFS
≥	Education	***	***	***	***	***	***	***	***	***
APPLICABILITY ¹	Office	**	**	**	***	***	***	***	**	***
PLICA	Healthcare	*	**	*	*	**	**	**	***	**
AP	Retail	**	**	***	***	***	***	***	**	***
	Sizes	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x1, 1x2, 6"x4, 1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x2, 1x4, 1x8, 2x2, 2x4
	Im/W (Max)	115	159	136	120	145	137	130	140	149
	Lum (Max)	5,300	6,900	7,000	6,500	6,200	10,000	6,400	9,300	8,500
	Life (@60K)	L84	L86	L86	L87	L82	L88	L87	L86	L88
INCE	Lens	Frost, Smooth	Frost, Smooth	Frost, Smooth	Frost, Smooth	Frost, Smooth	Frost - Smooth, Prismatic	Frost, Smooth	Frost, Smooth	Frost, Smooth
ORM/	Service from Below	No	No	No	No	Yes in Surface Mount	No	No	Yes	No
FEATURES / PERFORMANCE	Emergency	Remote	Remote	Remote	Remote	Integrated in Recessed Mount	Integrated	Integrated	Integrated	Remote
RES	CRI	80+	80+	80+/ 90+	80+	90+	80+/90+	80+	80+ / 90+	80+
ATU	Sensor Location	Tile Mount	Tile Mount	Tile Mount	Tile Mount	Tile Mount	Integrated	Integrated	Integrated	Tile Mount
	DLC	Standard	Standard	Standard	Standard	Standard/Premium	Premium	Premium	Standard	Standard/Premium
	Door	No - see CGSB	No - see CGSB	No - see CGSB	No - see CGSB	No - see CGSB	No - see CGSB	No - see CGSB	Yes	No - see CGSB
	Air Venting	No	No	No	No	No	No	No	No	Standard
	Lumen / CCT Select	No	Yes 💮	No	Yes 🌑	Yes 🌑	No	No	No	Yes 🌑
	VividTune™	No	No	No	No	No	No	No	No	No
ATED ROLS	WaveLinx LITE						~	•	~	✓
INTEGRATED	WaveLinx PRO						~	~	~	✓

Notes: 1. * * * = high applicability, * * = medium applicability, * = low applicability, blank = non-applicable. 2. CGTS-NUV also available (Canadian market only).

		Better										est ===
	on products learn more											*
		Center Basket CBRK	Flat Lens GR	Center Basket Achieva ARS	Center Basket Cruze CZS	Cruze ST	Cruze SB	RLN	Ovation	Accord	SkyRidge	Encounter
Ē	Education	***	***	***	***	***	***	**	**	*	*	**
	Office	**	**	**	***	***	**	***	***	***	***	***
APPLICABILITY¹	Healthcare	*	**	**	**	**	***	**	*	**	**	***
API	Retail	*	**	**	***	***	**	**	***	**	**	**
	Sizes	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x4, 2x2, 2x4	1x2, 1x4, 2x2, 2x4	1x2, 1x4, 2x2, 2x4, Metric
	Im/W (Max)	168	140	146	156	157	157	139	109	127	150	141
	Lumens (Max)	4,700	18,000	8,000	6,500	17,000	7,500	8,000	5,000	7,300	6,400	7,400
	Life (@60K)	L85	L89	L90	L90	L90	L84	L93	L89	L89	L92	L92
ANCE	Lens	Frost, Ribbed	Frost, Prismatic	Round or Square Ribbed	Round or Square, Frost - Ribbed or Smooth, Perf Inlays	Round or Square, Frost - Ribbed or Smooth, Perf Inlays	Round, Frost - Ribbed or Smooth	Frosted Acrylic	Metal Perforated	Frosted Acrylic	Acrylic (WaveStream)	Acrylic (WaveStream)
FEATURES / PERFORMANCE	Service from Below	Yes	Yes	No	No	No	Yes	Yes	No	Yes	No	No
PER	Emergency	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
ES /	CRI	80+	80+	80+/90	80+	80+ / 90	80+/90	80+ / 90	80+	80+	80+	80+ / 90
TOTA	Sensor Location	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Tile Mount	Integrated	Integrated	Integrated
E/	DLC	Premium	Standard / Premium	Standard / Premium	Standard / Premium	Standard / Premium	Premium	Premium	Standard	Premium	Premium	Premium
	Door	No	Yes	No - see Cruze SB	No - see Cruze SB	No - see Cruze SB	Yes	No	No	No	No	No
	Air Venting	Yes	No	No	Yes	Yes	No	No	Yes	Yes	Yes	Yes
	Lumen / CCT Select	Yes 🌑	Yes 🌑	Yes 🌑	Yes 🌑	No	Yes 😂	No	No	No	Yes 🌑	No
	VividTune™	No	Tunable White	No	No	Tunable White	Tunable White	Tunable White	No	No	No	Tunable White
ROLS	WaveLinx LITE	·	~	~	✓	·	~	✓			✓	~
INTEGRATED	WaveLinx PRO	·	~	~	~	~	✓	~	V	~	~	~

Notes: 1. $\star\star$ = high applicability, $\star\star$ = medium applicability, \star = low applicability, blank = non-applicable

		_ G ood			Bette				Best
Click to l	on products earn more								
		SLES ²	ST	ST2 DIM	SLSTP	SSRK Retrofit	SNX	SRL	MicroBay
	Education	**	*	**	***	*	***	***	***
Ē	Office	*	*	**	***	*	***	***	***
APPLICABILITY1	Healthcare				*	*	**	**	**
7	Retail	***	*	**	**	***	***	***	***
APF	Industrial	**	**	**	**	***	***	***	***
	Residential		***		**				
	Length	4', 8'	2', 4', 8'	2', 4', 8'	2', 4', 8'	4', 8'	2', 4', 8'	4', 8'	2', 4', 8'
	Im/W (Max)	167 (8ft)	108	122	148	159	176	149	175
	Lum (Max)	8,700	9,200	9,200	11,900	8,000 / 4 ft.	22,000	11,000	20,000
3	Life (@60K)	L70/50K ³	L70/50K	L70/50K	L70/50K	L94	L87	L82	L87
RMAN	Voltage	UNV	UNV	UNV	120V, UNV, NUV (120-347V)	UNV	UNV, 347, 480V	UNV, 347, 480V	UNV, 347, 480V
RFO	Dimming	N/A	No	0-10V	Triac or 0-10V ⁵	0-10V	0-10V, Step, Dali	0-10V, Step, Dali	0-10V, Dali
FEATURES / PERFORMANCE	Lens	None ⁴	White, Single or Dual Lens	White, Dual Lens	Diffuse, Poly	Frost, Acrylic	Open, Round, FDL, Square, Refl	Frost, Acrylic	Multiple
l iii	Emergency	Integrated	None	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
FEAT	CRI	80+	80+	80+	80+	80+	>80 / 90	80+	80+ / 90+
_	Sensor Location	Remote	Remote	Remote	Sensor Kit	N/A	Integrated	Integrated	Integrated
	DLC	Standard (TLED Lamps only)	Standard	Standard	Standard	Premium	Premium	Premium	Premium
	Lumen / CCT Select	No	No	© CCT	CCT/Lumen (No	Yes, specific lumen only	No	Optional 🌑
۵,,	Basic Occupancy				✓	'	✓	✓	V
INTEGRATED	Stand Alone Daylight / Occupancy					✓	✓	✓	✓
CON	WaveLinx LITE						✓	✓	✓
= -	WaveLinx						✓	✓	✓

Notes: 1. *\daggreen \daggreen \dagg LED light sources maintain at least 70% of their initial lumen output (B50, L70). 4. TLED CorePro lamp is glass tube. TLED MasterClass lamp is shatter resistant plastic. 5. 0-10V only applies to UNV or NUV inputs.

		Good			Better —			Best
Click to l	on products earn more							
		WP	NWS	WNLED	WSNLED	BCLED	AWS / AWWS	SWLED
	Education	**	***	***	**	**	***	***
ΙΔ	Office	*	**	**	***	*	***	***
\BIL	Healthcare	*	*	*	**	**	**	*
APPLICABILITY1	Retail	*	**	*	***	*	***	*
APP	Industrial	*	**	**			*	**
	Residential	***		*	*	*	**	
	Sizes	2' and 4', 5.1" wide	2', 4' / 5.3" wide	2', 4'	2', 4'	2', 4'	2', 4', 8' / 5.5" & 10" Wide	4'
	lm/W (Max)	114	129	118	108	120	165	150
SE	Lum (Max)	3,400	4,900	5,000	6,500	4,800	13,000	8,000
JAN	Life (@60K)	L70/50K	L82	L88	L87	L82	L90	L91
FEATURES / PERFORMANCE	Lens	Prismatic Acrylic	Diffuse, Acrylic	Frost, Acrylic	Frost + Film, Acrylic	Frost, Smooth	(Vandal Resistant) Ribbed Frost, Polycarb	(Vandal Resistant) Frost, Acrylic
/ PE	Emergency	No	Remote	Integrated	Integrated	Integrated	Integrated	Integrated
RES,	CRI	80+	80+	80+	80+	80+	80+, 90+	80+
ATUI	Row Mount	N/A	Yes	Yes	Yes	Yes	Yes	No
E.	Sensor Location	N/A	Integral, Microwave	N/A	N/A	N/A	Integrated	Integrated
	DLC	Standard	DLC, Title 24 Non-Res	Standard	Standard	None	DLC, Title 24 Res	Standard
	Lumen / CCT Select	No	CCT/Lumen 🌑	No	No	No	CCT/Lumen 🌑	No
	Basic Occupancy		~				✓	✓
INTEGRATED	Stand Alone Daylight / Occupancy						~	V
CON	WaveLinx LITE						✓	✓
	WaveLinx						✓	✓

Notes: 1. $\star\star\star$ = high applicability, $\star\star$ = medium applicability, \star = low applicability, blank = non-applicable

		Good —			Bette	r			Best =
	on products earn more				Silver of the second of the se				
		EZBY	SPHB	VHB	UHBS2	CZL	Steeler	OHB(L)	Benchmark
	Big Box Retail	*	***	*	***	***	**	***	*
-	Sports / Recreation	*	**	**	**	*	***	***	**
5	Warehouses	***	***	***	***	**	***	***	
APPLICABILITY	Manufacturing	**	**	**	***	*	***	***	***
PL	Cold Storage	*	**	***	***	*	*	***	**
AP	Large Indoor	*	**	*	**		**	***	**
	Complex Environments	*			**		*		***
	Lumen Range	18,000 - 30,000	9,000 - 60,000	9,000 - 48,000	12,000 - 36,000	5,000 - 32,000	9,000 - 30,000	9,000 - 100,000	12,000 - 70,000
	Selectable	Lumens/CCT 😁	Lumens/CCT	Lumens	Lumens/5CCT				
	Efficacy (Max)	150 lm/W	172 lm/W	164 lm/W	180 lm/W	176 lm/W	152 lm/W	205 lm/W	181 lm/W
_ н	CRI	80	70, 80, 90	70, 80, 90	80	80, 90	80, 90	70, 80, 90	70, 80
AN	Distribution	M	N, M, W	N, W	Selectable N, M, W	Multiple	N, M, W	N, M, W	N, M, W
B.M.	Sizes	13.4"	18", 26", 42"	< 2¹	12"/14.1"/16" Dia	4', 8'	17" Dia	Scalable	17", 25" Dia
IRF(Housing ²	Diecast	CRS	CRS / Extruded	Diecast	CRS	CRS / Diecast	CRS	Diecast
FEATURES / PERFORMANCE	Lensing	Acrylic	Polycarbonate	Polycarbonate	Polycarbonate	Multiple	Polycarbonate	Acrylic	Acrylic
RES	Uplight	None	Optional	None	None	Optional	Up to 10%	None	None
ATU	Life (@ 60K hrs)	L91	L88	L83	L91	L89	L88	L96	L92
围	Ambient Range	-20C to 50C	-40C to 55C	-40C to 55C	-40C to 50C	-40C to 65C	-40C to 55C	-40C to 55C	-40C to 65C
	Emergency	Remote	Integrated	Remote	Remote	Integrated	Remote	Integrated	Remote
	Ratings	IP65	Damp	Damp	IP65, NEMA 4X, NSF	Damp	IP65 Optics	Damp	IP66
	DLC	Premium	Premium	Standard, Premium	Premium	Premium	Premium	Premium	Premium
۵,,	Basic Occupancy			✓		✓	✓	'	✓
INTEGRATED	Stand Alone Daylight / Occupancy	Sensor Port	Sensor Port	✓	Sensor Port	·	~	·	✓
TEG	WaveLinx		· ·	~		~	· ·	'	V
So	Enlighted ³		✓	✓		✓	V	/	✓

Notes: 1. * * * = high applicability, * * = medium applicability, * = low applicability, blank = non-applicable 2. CRS=Cold-rolled Steel, Extruded=Extruded Aluminum, Diecast=Diecast Aluminum. 3. Location data for asset tracking.

		Good		Better —		Best I
Click to l	on products earn more					
		APVT-S	VT2	VT3	VT4S	VT4
	Canopy	**	**	**		
APPLICABILITY ¹	Storage	***	***	**		
	Parking Garage	**	**	***		
CAB	Warehouse	**	***	***	*	*
2	Food Processing	**	**	***	**	**
₹	Manufacturing		**	**	***	***
	Complex Environments		*	***	***	***
	Lumen Range	3,000 - 11,600	2,000 - 22,000	2,000 - 8,000	9,000 - 18,000	9,000 - 30,000
	Selectable	Lumens / CCT	N/A	Lumens / CCT	N/A	N/A
	Efficacy (Max)	151 lm/W	150 lm/W	154 lm/W	165 lm/W	146 lm/W
FEATURES / PERFORMANCE	Distribution ²	G	G, W	G, W, P	G	G
	Sizes	4', 8'	2', 4', 8'	2', 4'	2'	4'
2	Housing	Polycarbonate	Fiberglass/Polyester	Fiberglass/Polyester	Fiberglass	Fiberglass
	Lensing	Polycarbonate	DR Acrylic or Polycarb			
	Wet Location	Yes	Yes	Yes	Yes	Yes
	IP Rating	IP65	None	IP65, 66, 67	IP65, 66, 67, 69	IP65, 67
n E	NSF	None	Yes	Yes	Yes	Yes
2	NEMA 4X	None	None	None	Yes	Yes
-	Life (@60K hrs)	L89	L91	L91	L91	L92
	Ambient Range	-20C to 40C	-40C to 35C	-40C to 50C	-40C to 40C	-40C to 40C
	Emergency	Yes	Yes	Yes	Yes	Yes
	Vandal Resistant	None	Optional	Optional	Optional	Optional
	DLC	Standard	Premium	Premium	Premium	Premium
	Basic Occupancy	✓	✓	✓	✓	✓
CONTROLS	Stand Alone Daylight / Occupancy	V	V	V	~	V
N	WaveLinx	✓		✓		✓
0	LumaWatt Pro ³					

Notes: 1. ★★★ = high applicability, ★★ = medium applicability, ★ = low applicability, blank = non-applicable 2. G=General, W=Wide, P=Parking Garage.

3. Location data for asset tracking.

Lighting Brands

Ametrix

AtLite

Corelite

Ephesus

Fail-Safe HALO

HALO Commercial

Invue

iO

Iris

Lumark

LumarkAP

Lumière

McGraw-Edison

Metalux

MWS

NeoRay

Portfolio

PrentaLux - 3D Printed Lighting

RSA

Shaper

Streetworks

Sure-Lites

Controls Brands

Greengate

Fifth Light
Intelligent Lighting Controls

Connected Lighting Systems and Smart Spaces Platform

WaveLinx

Trellix Infrastructure



Cooper Lighting Solutions 1121 Highway 74 South Peachtree City, GA 30269 P: 770-486-4800 www.cooperlighting.com

Canada Sales 5925 McLaughlin Road Mississauga, Ontario L5R 1B8 P: 905-501-3000 F: 905-501-3172 © 2025 Cooper Lighting Solutions All Rights Reserved Printed in USA Publication No. BR519040EN-web October 6, 2025 2:01 PM Cooper Lighting Solutions is a registered trademark.

All other trademarks are property of their respective owners.

Product availability, specifications, and compliances are subject to change without notice.