CERTIFICATE OF COMPLIANCE

Certificate Number	UL-US-L76559-12-13809102-5
Report Reference	E76559-20190831
Date	14-Dec-2023
Issued to:	Cooper Lighting, LLC 1121 HIGHWAY 74 S PEACHTREE CITY, GA 30269-3019 United States
This is to certify that representative samples of	IFFX - Luminaire Fittings See Addendum Page for Product Designation(s).
	Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.
Standard(s) for Safety:	UL 1598, 5th Ed., Issue Date: 2021-03-26, Revision Date: 2021-06-18
Additional Information:	See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L76559-12-13809102-5
Report Reference E76559-20190831
Date 14-Dec-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
HC8, followed by 05 = 0500 lm fixed output (0.150 A), 07 = 0700 lm fixed output (0.200 A), 10 = 1000 lm fixed output (0.250 A), 15 = 1500 lm fixed output (0.350 A), 20 = 2000 lm fixed output (0.500 A), 25 = 2500 lm fixed output (0.650 A), 30 = 3000 lm fixed output (0.700 A), 35 = 3500 lm fixed output (0.875 A), 40 = 4000 lm fixed output (1.050 A), 45 = 4500 lm fixed output (1.140 A), 50 = 5000 lm fixed output (1.230 A), 55 = 5500 lm fixed output (1.320 A), 60 = 6000 lm fixed output (1.400 A) followed by D010 = 120-277V Driver, D010347 = 347V Driver, DLV = Low Voltage Driver followed by REM7,REM14,IEM7,IEM14,REMV7,REMV14,IEMV7,IEMV14 = Emergency Battery type (optional)	Luminaire Fittings - Rough-in Section
HC812R, followed by 05 = 0500 lm fixed output (0.150 A), 07 = 0700 lm fixed output (0.200 A), 10 = 1000 lm fixed output (0.250 A), 15 = 1500 lm fixed output (0.350 A), 20 = 2000 lm fixed output (0.500 A), 25 = 2500 lm fixed output (0.650 A), 30 = 3000 lm fixed output (0.700 A), 35 = 3500 lm fixed output (0.875 A), 40 = 4000 lm fixed output (1.050 A), 45 = 4500 lm fixed output (1.140 A), 50 = 5000 lm fixed output (1.230 A), 55 = 5500 lm fixed output (1.320 A), 60 = 6000 lm fixed output (1.400 A) followed by D010 = 120-277V Driver, D010347 = 347V Driver, DLV = Low Voltage Driver followed by REM7,REM14,IEM7,IEM14,REMV7,REMV14,IEMV7,IEMV14 = Emergency Battery type (optional)	Luminaire Fittings - Rough-in Section
HC8CP, followed by 05 = 0500 lm fixed output (0.150 A), 07 = 0700 lm fixed output (0.200 A), 10 = 1000 lm fixed output (0.250 A), 15 = 1500 lm fixed output (0.350 A), 20 = 2000 lm fixed output (0.500 A), 25 = 2500 lm fixed output (0.650 A), 30 = 3000 lm fixed output (0.700 A), 35 = 3500 lm fixed output (0.875 A), 40 = 4000 lm fixed output (1.050 A), 45 = 4500 lm fixed output (1.140 A), 50 = 5000 lm fixed output (1.230 A), 55 = 5500 lm fixed output (1.320 A), 60 = 6000 lm fixed output (1.400 A) followed by D010 = 120-277V Driver, D010347 = 347V Driver, DLV = Low Voltage Driver followed by	Luminaire Fittings - Rough-in Section

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L76559-12-13809102-5
Report Reference E76559-20190831
Date 14-Dec-2023

REM7,REM14,IEM7,IEM14,REMV7,REMV14,IEMV7,IEMV14 = Emergency Battery type (optional)	
HC8R, followed by 05 = 0500 lm fixed output (0.150 A), 07 = 0700 lm fixed output (0.200 A), 10 = 1000 lm fixed output (0.250 A), 15 = 1500 lm fixed output (0.350 A), 20 = 2000 lm fixed output (0.500 A), 25 = 2500 lm fixed output (0.650 A), 30 = 3000 lm fixed output (0.700 A), 35 = 3500 lm fixed output (0.875 A), 40 = 4000 lm fixed output (1.050 A), 45 = 4500 lm fixed output (1.140 A), 50 = 5000 lm fixed output (1.230 A), 55 = 5500 lm fixed output (1.320 A), 60 = 6000 lm fixed output (1.400 A) followed by D010 = 120-277V Driver, D010347 = 347V Driver, DLV = Low Voltage Driver followed by REM7,REM14,IEM7,IEM14,REMV7,REMV14,IEMV7,IEMV14 = Emergency Battery type (optional)	Luminaire Fittings - Rough-in Section
HC8RCP, followed by 05 = 0500 lm fixed output (0.150 A), 07 = 0700 lm fixed output (0.200 A), 10 = 1000 lm fixed output (0.250 A), 15 = 1500 lm fixed output (0.350 A), 20 = 2000 lm fixed output (0.500 A), 25 = 2500 lm fixed output (0.650 A), 30 = 3000 lm fixed output (0.700 A), 35 = 3500 lm fixed output (0.875 A), 40 = 4000 lm fixed output (1.050 A), 45 = 4500 lm fixed output (1.140 A), 50 = 5000 lm fixed output (1.230 A), 55 = 5500 lm fixed output (1.320 A), 60 = 6000 lm fixed output (1.400 A) followed by D010 = 120-277V Driver, D010347 = 347V Driver, DLV = Low Voltage Driver followed by REM7,REM14,IEM7,IEM14,REMV7,REMV14,IEMV7,IEMV14 = Emergency Battery type (optional)	Luminaire Fittings - Rough-in Section

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number	UL-CA-L76559-32-13809102-5
Report Reference	E76559-20190831
Date	14-Dec-2023
Issued to:	Cooper Lighting, LLC 1121 HIGHWAY 74 S PEACHTREE CITY, GA 30269-3019 United States
This is to certify that representative samples of	IFFX7 - Luminaire Fittings Certified for Canada See Addendum Page for Product Designation(s).
	Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.
Standard(s) for Safety:	CSA C22.2 NO. 250.0:21, 5th Ed., Issue Date: 2021-03-26, Revision Date: 2021-06-18
Additional Information:	See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L76559-32-13809102-5
Report Reference E76559-20190831
Date 14-Dec-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
HC8, followed by 05 = 0500 lm fixed output (0.150 A), 07 = 0700 lm fixed output (0.200 A), 10 = 1000 lm fixed output (0.250 A), 15 = 1500 lm fixed output (0.350 A), 20 = 2000 lm fixed output (0.500 A), 25 = 2500 lm fixed output (0.650 A), 30 = 3000 lm fixed output (0.700 A), 35 = 3500 lm fixed output (0.875 A), 40 = 4000 lm fixed output (1.050 A), 45 = 4500 lm fixed output (1.140 A), 50 = 5000 lm fixed output (1.230 A), 55 = 5500 lm fixed output (1.320 A), 60 = 6000 lm fixed output (1.400 A) followed by D010 = 120-277V Driver, D010347 = 347V Driver, DLV = Low Voltage Driver followed by REM7,REM14,IEM7,IEM14,REMV7,REMV14,IEMV7,IEMV14 = Emergency Battery type (optional)	Luminaire Fittings - Rough-in Section
HC812R, followed by 05 = 0500 lm fixed output (0.150 A), 07 = 0700 lm fixed output (0.200 A), 10 = 1000 lm fixed output (0.250 A), 15 = 1500 lm fixed output (0.350 A), 20 = 2000 lm fixed output (0.500 A), 25 = 2500 lm fixed output (0.650 A), 30 = 3000 lm fixed output (0.700 A), 35 = 3500 lm fixed output (0.875 A), 40 = 4000 lm fixed output (1.050 A), 45 = 4500 lm fixed output (1.140 A), 50 = 5000 lm fixed output (1.230 A), 55 = 5500 lm fixed output (1.320 A), 60 = 6000 lm fixed output (1.400 A) followed by D010 = 120-277V Driver, D010347 = 347V Driver, DLV = Low Voltage Driver followed by REM7,REM14,IEM7,IEM14,REMV7,REMV14,IEMV7,IEMV14 = Emergency Battery type (optional)	Luminaire Fittings - Rough-in Section
HC8CP, followed by 05 = 0500 lm fixed output (0.150 A), 07 = 0700 lm fixed output (0.200 A), 10 = 1000 lm fixed output (0.250 A), 15 = 1500 lm fixed output (0.350 A), 20 = 2000 lm fixed output (0.500 A), 25 = 2500 lm fixed output (0.650 A), 30 = 3000 lm fixed output (0.700 A), 35 = 3500 lm fixed output (0.875 A), 40 = 4000 lm fixed output (1.050 A), 45 = 4500 lm fixed output (1.140 A), 50 = 5000 lm fixed output (1.230 A), 55 = 5500 lm fixed output (1.320 A), 60 = 6000 lm fixed output (1.400 A) followed by D010 = 120-277V Driver, D010347 = 347V Driver, DLV = Low Voltage Driver followed by	Luminaire Fittings - Rough-in Section

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L76559-32-13809102-5
Report Reference E76559-20190831
Date 14-Dec-2023

REM7,REM14,IEM7,IEM14,REMV7,REMV14,IEMV7,IEMV14 = Emergency Battery type (optional)	
HC8R, followed by 05 = 0500 lm fixed output (0.150 A), 07 = 0700 lm fixed output (0.200 A), 10 = 1000 lm fixed output (0.250 A), 15 = 1500 lm fixed output (0.350 A), 20 = 2000 lm fixed output (0.500 A), 25 = 2500 lm fixed output (0.650 A), 30 = 3000 lm fixed output (0.700 A), 35 = 3500 lm fixed output (0.875 A), 40 = 4000 lm fixed output (1.050 A), 45 = 4500 lm fixed output (1.140 A), 50 = 5000 lm fixed output (1.230 A), 55 = 5500 lm fixed output (1.320 A), 60 = 6000 lm fixed output (1.400 A) followed by D010 = 120-277V Driver, D010347 = 347V Driver, DLV = Low Voltage Driver followed by REM7,REM14,IEM7,IEM14,REMV7,REMV14,IEMV7,IEMV14 = Emergency Battery type (optional)	Luminaire Fittings - Rough-in Section
HC8RCP, followed by 05 = 0500 lm fixed output (0.150 A), 07 = 0700 lm fixed output (0.200 A), 10 = 1000 lm fixed output (0.250 A), 15 = 1500 lm fixed output (0.350 A), 20 = 2000 lm fixed output (0.500 A), 25 = 2500 lm fixed output (0.650 A), 30 = 3000 lm fixed output (0.700 A), 35 = 3500 lm fixed output (0.875 A), 40 = 4000 lm fixed output (1.050 A), 45 = 4500 lm fixed output (1.140 A), 50 = 5000 lm fixed output (1.230 A), 55 = 5500 lm fixed output (1.320 A), 60 = 6000 lm fixed output (1.400 A) followed by D010 = 120-277V Driver, D010347 = 347V Driver, DLV = Low Voltage Driver followed by REM7,REM14,IEM7,IEM14,REMV7,REMV14,IEMV7,IEMV14 = Emergency Battery type (optional)	Luminaire Fittings - Rough-in Section

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/